



DCA-60SPH



DCA-90SPH



DCA-115SPK



DCA-125SPM



DCA-150SPH

型式	DCA-60SPH DCA-60SPI		DCA-75SPI		DCA-90SPH		DCA-110SPN		DCA-115SPK		DCA-125SPM		DCA-150SPH DCA-150SPK															
●交流発電機																												
周波数 Hz	50	60	50	60	50	60	50	60	50	60	50	60	50	60														
出力 kVA	50	60	65	75	75	90	95	110	100	115	100	125	125	150														
電圧 V	200	220	200	220	200	220	200/400	220/440	200/400	220/440	200/400	220/440	200/400	220/440														
電流 A	144	157	188	197	217	236	274/137	289/144	289/144	302/151	289/144	328/164	361/180	394/197														
力率	0.8(遅れ)																											
相数	三相4線式																											
励磁方式	ブラシレス(AVR付)																											
極数	4																											
単相電圧 V	100	110	100	110	100	110	100	110	100	110	100	110	100	110														
出力□ 出力kVA	7.5×2		10.0×2																									
●ディーゼルエンジン																												
名称	日野W06E-H いすゞA-6BG1		いすゞA-6BG1		日野H07D-C		日産A-FE6T		コマツS6D102E-1-A		三菱6D16-TEZ		日野M10C-TB コマツS6D108E-2-A															
形式 ※1	直接噴射式						直接噴射式・ターボ付																					
気筒数-内径×行程 mm	6-104×118 6-105×125		6-105×125		6-110×130		6-108×128		6-102×120		6-118×115		6-127×130 6-108×130															
総排気量 L	6.014 6.494		6.494		7.412		6.925		5.88		7.545		9.880 7.150															
定格出力 kW[PS]	48.5[66] 47.1[64]		57.4[78]		58.8[80]		68.4[93]		69.9[95]		83.1[113]		84.8[115]		108[144]		92.7[126]		104[142]		107[145]		122[166]		113[153]		135[183]	
回転数 min	1500		1800		1500		1800		1500		1800		1500		1800		1500		1800		1500		1800		1500		1800	
燃料	軽油又はA重油																											
燃料タンク容量 L	125		155		185		210		240		250		250															
燃料消費量 ※2 L/hr	5.9/8.2 7.1/9.0		7.6/10.1 9.1/11.4		7.8/10.8		9.3/12.5		8.8/12.3		11.1/15.0		10.8/14.9		12.8/17.9		10.6/15.1		12.6/17.5		11.2/15.9		14.4/21.2		13.7/19.8		18.1/26.1	
冷却水容量 L	18 26		27.4		22.6		27.4		21.5		28.3		33.2 29.4															
潤滑油量 L	20 19.3		19.3		22.5		12.5		22		13.5		26.5 31															
バッテリー×個	95E41R×2						115F51×2						65D31R×2		115F51×2													
●寸法・質量																												
全長 mm	2420		2630		2900		2850		2900		3100		3270 3350															
全幅 mm	880		1000		1100		1050		1050		1080		1180 1200															
全高 mm	1250		1300		1400		1400		1450		1500		1500															
乾燥質量 kg	1400[1610] 1410[1610]		1590[1780]		1975[2230]		2000[2270]		2020[2280]		2180[2580]		2500[2930] 2740[3050]															
●騒音値																												
7m/dB(A) (1800min) 無負荷	65 66		64		64		67		65.9		66		67															

単相出力□は単相出力コンセント (1.5kVA×2) と出力端子の合計です。

※1 すべて水冷4サイクルです。 ※2 50%/75%負荷時の値です。 ●仕様は予告なく変更することがあります。